

E1
D1
Encl

a gate insulating film on the first substrate;
a passivation film on the gate insulating film including the first substrate;
a pixel electrode in the pixel region, wherein the pixel electrode is divided into a plurality of domains;
a light-shielding layer on the second substrate;
a color filter layer on the light-shielding layer;
a common electrode on the color filter layer;
a plurality of electric field distortion dielectric structures in the plurality of domains, wherein the dielectric structure in the neighboring domains have unequal shapes; and
an alignment film on at least one of the first and second substrates.

D2
Sub
E1

4. (Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define a pixel region;
a common auxiliary electrode on a layer equal to the gate lines to surround the pixel region;
a gate insulating film on the first substrate;
a passivation film on the gate insulating film including the first substrate;
a pixel electrode in the pixel region, wherein the pixel electrode is divided into a plurality of domains; the pixel electrode not overlapping the common auxiliary electrode;
a light-shielding layer on the second substrate;
a color filter layer on the light-shielding layer;
a common electrode on the color filter layer;

E1
D2
End

a plurality of electric field distortion dielectric structures in the plurality of domains,
wherein the dielectric structure in the neighboring domains have unequal shapes; and
an alignment film on at least one of the first and second substrates.

Sub E1
D3

8. (Amended) The multi-domain liquid crystal display device as claimed in claim 1,
further comprising a thin film transistor formed in a crossing point of the gate lines and the data
lines.

D4
Sub E1

12. (Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise,
to define a pixel region;
a common auxiliary electrode on a layer equal to the gate lines to surround the pixel
region;
a gate insulating film on the first substrate;
a passivation film on the gate insulating film including the first substrate, the pixel
electrode having an electric field induction window therein;
a pixel electrode in the pixel region, wherein the pixel electrode is divided into a plurality
of domains;
a light-shielding layer on the second substrate;
a color filter layer on the light-shielding layer;
a common electrode on the color filter layer;
a plurality of electric field distortion dielectric structures in the plurality of domains,
wherein the dielectric structure in the neighboring domains have unequal shapes; and

an alignment film on at least one of the first and second substrates.

E1
Dy
Cont'd

13. (Amended) A multi-domain liquid crystal display device comprising:

- first and second substrates opposing each other between a liquid crystal layer;
- a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define a pixel region;
- a common auxiliary electrode on a layer equal to the gate lines to surround the pixel region;
- a gate insulating film on the first substrate;
- a passivation film on the gate insulating film including the first substrate, the passivation film having an electric field induction window therein;
- a pixel electrode in the pixel region, wherein the pixel electrode is divided into a plurality of domains;
- a light-shielding layer on the second substrate;
- a color filter layer on the light-shielding layer;
- a common electrode on the color filter layer;
- a plurality of electric field distortion dielectric structures in the plurality of domains, wherein the dielectric structure in the neighboring domains have unequal shapes; and
- an alignment film on at least one of the first and second substrates.

14. (Amended) A multi-domain liquid crystal display device comprising:

- first and second substrates opposing each other between a liquid crystal layer;
- a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define a pixel region;

a common auxiliary electrode on a layer equal to the gate lines to surround the pixel region;

E1
D4
Cent'd
a gate insulating film on the first substrate, the gate insulating film having an electric field induction window therein;

a passivation film on the gate insulating film including the first substrate;

a pixel electrode in the pixel region, wherein the pixel electrode is divided into a plurality of domains;

a light-shielding layer on the second substrate;

a color filter layer on the light-shielding layer;

a common electrode on the color filter layer;

a plurality of electric field distortion dielectric structures in the plurality of domains, wherein the dielectric structure in the neighboring domains have unequal shapes; and

an alignment film on at least one of the first and second substrates.

15. (Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define a pixel region;

a common auxiliary electrode on a layer equal to the gate lines to surround the pixel region;

a gate insulating film on the first substrate;

a passivation film on the gate insulating film including the first substrate;

a pixel electrode in the pixel region, wherein the pixel electrode is divided into a plurality of domains;

E1
Dy
Cont'd

- a light-shielding layer on the second substrate;
- a color filter layer on the light-shielding layer;
- a common electrode on the color filter layer, the common electrode having an electric field induction window therein;
- a plurality of electric field distortion dielectric structures in the plurality of domains, wherein the dielectric structure in the neighboring domains have unequal shapes; and
- an alignment film on at least one of the first and second substrates.

16. (Amended) A multi-domain liquid crystal display device comprising:

- first and second substrates opposing each other between a liquid crystal layer;
- a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise, to define a pixel region;
- a common auxiliary electrode on a layer equal to the gate lines to surround the pixel region;
- a gate insulating film on the first substrate;
- a passivation film on the gate insulating film including the first substrate;
- a pixel electrode in the pixel region, wherein the pixel electrode is divided into a plurality of domains;
- a light-shielding layer on the second substrate;
- a color filter layer on the light-shielding layer, the color filter layer having an electric field induction window therein;
- a common electrode on the color filter layer;
- a plurality of electric field distortion dielectric structures in the plurality of domains, wherein the dielectric structure in the neighboring domains have unequal shapes; and

an alignment film on at least one of the first and second substrates.

E1
Q3

18. (Amended) A multi-domain liquid crystal display device comprising:
first and second substrates opposing each other between a liquid crystal layer;
a plurality of gate bus lines and data lines on the first substrate lengthwise and crosswise,
to define a pixel region;
a common auxiliary electrode on a layer equal to the gate lines to surround the pixel
region;
a gate insulating film on the first substrate;
a passivation film on the gate insulating film including the first substrate;
a pixel electrode in the pixel region, wherein the pixel electrode is divided into a plurality
of domains;
a light-shielding layer on the second substrate;
a color filter layer on the light-shielding layer;
an over coat layer on the color filter layer, the over coat layer having an electric field
induction window therein;
a common electrode on the over coat layer;
a plurality of electric field distortion dielectric structures in the plurality of domains,
wherein the dielectric structure in the neighboring domains have unequal shapes; and
an alignment film on at least one of the first and second substrates.

Q6
Q5
E1

37. (Amended) A multi-domain liquid crystal display device comprising:
a data line to apply a data signal;
a pixel electrode for driving a liquid crystal, wherein the pixel electrode is divided into a

plurality of domains, the pixel electrode having an electric field induction window therein;
a gate line crossed to the data line, to define a pixel region;
a common auxiliary electrode formed to surround the pixel region; and
a plurality of electric field distortion dielectric structures in the plurality of domains,
wherein the dielectric structure in the neighboring domains have unequal shapes.
